

BC Textile Innovations Inc.

Website: www.textileinnovations.com

312-1952 Kingsway Avenue Port Coquitlam, BC V3C 6C2 604-552-7671 Fax: 604-552-7646

Jan 2016

MATERIAL SAFETY DATA SHEET

I. PRODUCT IDENTIFICATION

Product Name: NuSolvent Chemical Name: Trade Secret

Chemical Family: N/A
Formula: N/A
Molecular Weight: N/A
Synonyms: None

Caution: The user should conduct his/her own experiments and establish proper

procedures and control before attempting use on critical parts.

II. EMERGENCY CONTACT

ONLY IN THE EVENT OF CHEMICAL EMERGENCIES INVOLVING A SPILL, LEAK, FIRE, EXPOSURE, OR ACCIDENT INVOLVING CHEMICALS

(604) 552-7671 / (604) 552-7674 / (866) 552-7671 / (604) 787-5776 / FAX / (604) 552-7646

III. PHYSICAL DATA (Determined on Typical Data)

Boiling Point: 310 °F to 320 °F Specific Gravity: 0.858 to 0.863 Vapor Pressure: (20 °C) 3mmHg Percent volatile by Volume: 60 to 95% Emulsifies

Physical Description: Clear white to yellow liquid with citrus odor

Evaporation Rate: Medium to Fast

IV. INGREDIENTS

Chemical Name	CAS No.		% Weight	Exposure Limit
Citrus Terpenes 6864	7-72-3	65	to 97	N/E
Proprietary components	Trade Secret		3 to 35	N/E

Note: - All components are from plant based sources.

- Major components are rated GRAS by USFDA.
- Readily biodegradable.

NuSolvent

V. FIRE AND EXPLOSION HAZARD DATA

Flash Point: 130 °F

Flammable Limits: LEL approx. 0.7% UEL Approx. 6.1% **Extinguishing Media:** Carbon Dioxide, Foam or Dry Chemical

Special Fire Fighting

Procedures: SCBA recommended, smother to exclude air, DO NOT use water,

e as an oil fire.

Unusual Fire Fighting

Hazards: Combustible liquid, keep away from heat, sparks, and open flames;

against spontaneous combustion.

Incompatibility

handl

guard

(Material to avoid): Strong oxidizing agents and acidic agents including acidic clays, peroxid es, halogens, vinyl chloride, and iodine pentafluoride.

Hazardous Decomposition

Materials: Smoke may be acrid and fume irritating, burning generates carbon

monoxide, carbon dioxide, and smoke.

Hazardous Polymerization: None Described

Stability Considerations: Stable

Conditions to Avoid for

Stability: Avoid temperatures over 115 °F

VI. HEALTH HAZARD DATA

Effects of Over Exposure: Product is harmful if swallowed, ingestion may cause vomiting, headache,

and other medical problems; may be irritating to skin and eyes. Skin contact may cause slight redness. Contains a possible skin sensitizer, eye contact can cause moderate to high irritation. Inhalation can cause nose, throat, and respiratory tract irritation, coughing, headache. Prolonged or repeated exposure can cause drying, defatting, and dermatitis of skin.

Signs and Symptoms of

Over Exposure: Product may be irritating to the skin, eyes, nose, and throat.

Medical Conditions Generally

aggravated by exposure: Persons with allergies or pre-existing conditions should avoid contact

with this product.

Emergency & First Aid Procedures:

Eyes: Remove contact lenses at once. Flush with water for at least 15 minutes. If irritation persists seek

medical attention.

Skin: Wash affected area with copious amounts of soap and water. If irritation develops, seek medical

attention.

Ingestion: Seek medical attention immediately. DO NOT induce vomiting. Rinse mouth with water, then drink one glass of water. DO NOT leave victim unattended. Never give anything by mouth if victim

is unconscious, is rapidly losing consciousness, or is convulsing.

Inhalation: If symptoms of overexposure are experienced, evacuate to fresh air. If symptoms persist, seek medical attention.

VII. SPILL OR LEAK PROCEDURES

Steps to be taken if material is released or spilled: Mop up or otherwise absorb, move leaking containers to well-ventilated area or transfer into a secure container. No smoking. Eliminate any source of ignition, minimize inhalation. Use NIOSH approved respiratory protection device, CAUTION slippery on floor.

Waste Disposal Method: Incinerate or dispose in accordance with Local, State, and Federal Regulations. Taking regulations into consideration, waste may be incinerated or handled through EPA Spill Control Plan via landfill or dilution.

MATERIAL SAFETY DATA SHEET (Cont.)

NuSolvent

VIII. SPECIAL PROTECTION INFORMATION

Respiratory Protection: Not normally required. If vapor concentration becomes high, use NIOSH

approved respirators.

Ventilation:Useas desiredSkin Protection:Oil resistant glovesEye Protection:Oil resistant goggles

Other Protective Equipment: Oil resistant apron, emergency eye wash and shower stations

Appropriate Hygienic

Practices: Wash thoroughly after handling. Launder contaminated clothing before

re-use.

IX. TRANSPORTATION INFORMATION

TDG Status: Hazardous DOT Label/Placard [exemption § 173.150(f) applies: Highway/Rail: per requirements for Combustible Liquids Air/Ship: per requirements for Flammable Liquids

SHIPPING CLASSIFICATION:

Proper Shipping Name: TERPENE HYDROCARBONS, N.O.S.

Hazard Class: 3

Identification No: UN231 9

Packing Group: III

The listed transportation classification does not address regulatory variations due to changes in package size, mode of shipment or other regulatory descriptions.

National Fire Protection Association Hazard Rating: 1 Health Hazard - Slight

2 Flammability - Moderate0 Reactivity - Minimal

X. PACKAGING

NuSolvent may be packaged in epoxy-lined containers or fluorinated plastic containers.

XI. STORAGE AND HANDLING

Handling and Storage Precautions: Store in a warehouse with a fire prevention system. Avoid contact with incompatible chemicals listed in Section IV. Store in tightly sealed full containers in well-ventilated controlled warehouse conditions. Partially filled containers should be blanketed with nitrogen.

Other Precautions: Product may expand slightly in storage causing pressure to build in container. Open container carefully if product appears to be under pressure. Drum lining may occasionally chip and fall to bottom of container after long storage or excessive handling. As a precaution, pour liquid through filter/strainer to catch small pieces of liner before blending or repackaging. Commercially clean empty containers before re-use. CAUTION: Do not weld or cut empty containers (Vapors May Ignite).

The informati on contained herein is based on current know ledge and experience: no responsibility is accepted that the information is sufficient or correct in all cases. Users should consider these data only as a supplement to othe r information obtained by the user. No warranty is expressed or implied regarding the accuracy of this data, the results to be obtained from the use thereof, or that any such use will not infringe any patent. Users should make independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials, the safety and health of employees and customers, and the protection of the environment. This information is furnished upon the condition the person receiving it shall determine the suitability for the particular purpose. This MSDS is to be used as a guideline for safe work practices and emergency response.